## **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

- 1-13. (Cancelled)
- 14. (Previously Presented) The method of claim 16 wherein the bath comprises at least one additional silane coupling agent, namely, a chloro-silane coupling agent and the boric acid is present in the range from about 0.1% to 5% of the combined weight of said coupling agents.
  - 15. (Cancelled)
- 16. (Currently Amended) The method of claim 13 28 wherein said weak acid is boric acid.
  - 17-22. (Cancelled)
  - 23-26. (Cancelled)
- 27. (Currently Amended) The An epoxy resin article reinforced with fabric finished according to the method of claim 23 28 wherein the article is a circuit board.
- 28. **(New)** A method of finishing a glass fabric that is used for reinforcing an epoxy resin article comprising the steps of:
  - a) providing fabric woven from glass fiber;
  - cleaning said fabric to remove sizing and other deposits on the surface of the filaments in the glass fiber;

Appl. No. 10/625,261

Amdt. dated November 28, 2005

Reply to Final Action of November 4, 2005

- c) preparing a bath for said fabric comprising water and at least one cationic amino-silane coupling agent.
- d) immersing said cleaned fabric in said bath;
- e) removing the fabric from the bath and removing excess bath solution;
- f) drying the fabric;
- g) immersing the finish and dried fabric in a solution of a weak acid; for complexing the amino function of said agent; and,
- h) drying the fabric whereby said fabric when used to reinforce an epoxy article will produce an article with substantially reduced voids.